

Selleys No More Cracks: Exterior Brick and Render

Description

Selleys No More Cracks Exterior Brick and Render is a ready to use filler that dries to a durable render texture finish. It easily repairs deep, wide cracks, chips, holes and small shallow surface imperfections on exterior masonry surfaces. It can be tooled to a render texture or sanded to a smooth finish.

For thin applications (2-3mm) allow to dry for 2-3 hours depending on humidity. For deeper holes apply in 10 mm layers allowing each layer to dry before applying the next.

Can be painted over with water or oil based paints. Allow longer drying times if painting with oil based paints, for deeper applications or in colder weather. Protect from rain until dry.

Product Information

Packaging	Size
Tub	500 g

Tips

For a smoother texture, sand surface after drying.

For best results apply an undercoat before your top coat of paint.

Where movement occurs use Selleys Paint Over Sealant.

Uses

For use on exterior masonry surfaces such as bricks, concrete and cement render.

Clean Up

Clean tools and hands with water before the filler dries.

Features

- Durable
- For use on exterior masonry surfaces
- Can be tooled to a render texture or sanded to a smooth finish
- Can be painted with water and oil based paints.
- Easy to sand
- Easy to apply

Storage

Close lid tightly after use and store in a cool dry place.

Limitations

- Do not use below 5 °C.

Technical Details

Property	Typical Result
Technology	Water Based
Colour	Grey
Sanding/Painting Time	2-3 hours for a 2-3 mm application.
Indicative data only, not intended for preparation of specifications	

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com

Surface Preparation

Ensure that the surface to be filled is clean and dry with no loose powdery material.

Directions for Use

Use a filling blade or trowel to press filler into hole and tool to a feathered edge.