

## SELLEYS 3 IN 1 WHITE

### Description

Selleys 3 in 1 is an adhesive, sealant and gap filler which uses the latest technology to deliver the most versatile product. It is perfect for virtually any sealing, bonding and filling applications and for virtually any surface. Selleys 3 in 1 is a high strength construction adhesive, a waterproof sealant and no shrink gap filler – all in one.

### Product Information

Packaging	Size	Colour
Cartridge	480 grams	White

### Uses

- Sealing, bonding and filling
- Suitable for wet or dry surfaces
- Interior/exterior use
- Use for glass, metal, timber, brick, concrete, tiles and most plastics<sup>#</sup>

### Technical Features

- High strength bond
- Water and weather resistance
- Excellent adhesion
- Highly durable
- Highly versatile
- Interior & exterior
- Paintable
- Non-cracking
- UV Resistant
- Mould resistant
- Fast grab
- Low VOC

### Technical Details

Property	Typical Result
<b>Technology</b>	Moisture curing silyl-modified polymer (SMP)
<b>Colour</b>	White
<b>Density</b>	~1.65
<b>Application Temperature</b>	5 to 30°C
<b>Tooling Time (23°C, 50% R.H.)</b>	~15minutes
<b>Skin Time (23°C, 50% R.H.)</b>	15 to 30minutes
<b>Cure Rate (23°C, 50% R.H.)</b>	3 to 4mm/24hrs
<b>Slump</b>	0mm
<b>Tensile Strength (DIN 53504)</b>	1.3MPa
<b>Shore A Hardness</b>	40 ± 5
<b>Elongation at Break (DIN 53504)</b>	>250%
<b>Modulus at 100% Elongation (DIN 53504)</b>	~0.8MPa
<b>Movement Capability (ISO9046 modified)</b>	± 20%
<b>Service Temperature</b>	0 to 70°C
<b>VOC Content (By theoretical calculations)</b>	~34g/L
Indicative data only, not intended for preparation of specifications	

### Surface Preparation

Ensure surface is clean, dry and free from dust, grease, old or crumbling sealant.

# SELLEYS 3 IN 1 WHITE

---

## Directions for Use

Cut tip and attach nozzle. Insert in caulking gun. Cut nozzle to required size.

### *Adhesive*

Apply to one surface, in beads for broad surfaces (every 30cm) or dots for small surfaces. Press surfaces together and allow to cure.

### *Sealant*

Apply product, ensuring it is forced into the joint, with good contact to surfaces. Tool with a soap solution before skinning occurs.

### *Filler*

Apply product into gap. Smooth off with spatula dipped in soapy water. Allow to skin before painting with water-based paints

## Tips

For neater joints, mask sides before applying sealant and remove tape before sealant skins.

Larger, heavier items need to be supported until the adhesive cures.

## Clean Up

Uncured product may be removed with mineral turps. Cured product can be removed by scraping or sanding or with the help of Silicone Remover.

## Storage

Store in cool, dry conditions below 30°C.  
Use within 6 months of opening

## Limitations

Cannot be painted with solvent based paints. If required, paint with a water-based paint first.

#Not for Polyethylene, Polypropylene or Teflon.

## Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)