

No More Gaps® Bathroom and Kitchen

Description

Selleys No More Gaps Bathroom & Kitchen is the ideal solution for filling gaps and cracks around skirting boards, cabinets, cornices, and inside window & door frames in damp and humid areas. It has been formulated to be water resistant, with a fungicide to protect against unsightly mould growth.

Product Information

Packaging	Size	Colour
Cartridge	410 grams	White

Uses

It is suitable for materials such as ceramics, glass, aluminium, plasterboard, wood, particle board and cement sheeting.

Features

- Superior water and mould resistance
- Superior Flexibility
- Ideal for damp and humid areas
- Protects against mould

Technical Details

Property	Typical Result
Technology	Water based
Colour	White
Appearance	Smooth paste
Application Temperature	At least 5°C
Skin time	20 min
Density	1.5
Joint Movement capability	+/- 25%
Elongation ASTM D412	>200%
Shore A Hardness ASTM D2240	25
Paint over time (gloss, sheen, low sheen)	60 min*
Paint over time (flat, ceiling)	180 min*
Indicative data only, not intended for preparation of specifications	

Directions for Use

1. Ensure surfaces are clean, dry and free from dust or grease
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle
3. Insert cartridge into caulking gun
4. Apply with caulking gun, pushing product into gap or joint
5. Smooth with a wet gloved finger/spatula

Tips

Allow surface to skin prior to painting (approx. 1 hour*).

*To avoid paint cracking, apply to gaps (no larger than 5mm deep and 10mm wide) at temperatures above 10°C. Allow sealant to dry before painting over. Avoid applying paint too thickly. Allow 24–48hrs before painting with oil-based paints. Longer drying times are required for flat and ceiling paints because they are highly filled (i.e. contains lower binder content than other paints). This means the paint does not flex as much when the sealant dries. May be applied to damp surfaces but product and surface must then be allowed to dry.

Clean Up

Wet – Clean up using damp cloth.

Dry – Clean up using scraper.

Limitations

Use Selleys Wet Area Silicone Sealant for gaps around baths, sinks & showers to create a waterproof seal.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com