

## Selleys Wet Area Silicone

### Description

Selleys Wet Area Silicone Sealant is ideal for use in bathrooms, kitchens and laundries and delivers a superior waterproof and mould resistant seal that will not shrink, crack or peel away, guaranteed for 25 years\*.

- Low VOC (Meets Green Building Council of Australia limits for General Purpose Adhesives and Sealants < 50g/L)

### Product Information

Packaging	Size	Colour
Cartridge	300g	Clear
Cartridge	300g	Black
Cartridge	300g	Dark Grey
Cartridge	300g	Light Grey
Cartridge	300g	Off White
Cartridge Twin Pack	300g x 2	White
Cartridge Triple Pack	300g x 3	White
Cartridge	300g	White
Cartridge	300g	Ivory
Tube	90mL	White
Tube	90mL	Clear
Tube	75g	White

### Uses

Wet Area Silicone Sealant is ideal for use on or around showers, baths, spas, plumbing fixtures and sinks. It will work on materials such as ceramic, glazed & porcelain fixtures, metal, copper & brass fittings, powder coated aluminium, aluminium, plastic laminates, rubber, glass, stainless steel and concrete.

### Features

- 100% Silicone Sealant
- 25 year guarantee against cracking & peeling\*
- Superior waterproof seal
- Neutral cure

### Technical Details

Property	Typical Result
<b>Technology</b>	Neutral cure silicone
<b>Colour</b>	Various
<b>Density</b>	1.04
<b>Skin Time</b> 25°C / 50% RH	5 – 10 minutes
<b>Slump</b> JIS A 1439	No Slump (0.1% max)
<b>Shore A Hardness</b>	18 – 21
<b>Elongation at Break</b> ASTM D412	350% - 450%
<b>Movement Capability</b> ISO9047	+/- 25%
<b>Service Temperature</b>	-40 – 150°C
<b>VOC Content</b>	<50 g/L
Indicative data only, not intended for preparation of specifications	

### Surface Preparation

Surfaces must be clean, dry, and free of dirt, grease, oil or water. Clean surface with turps and allow to completely dry.

### Directions for Use

1. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle.
2. Place in caulking gun, and apply with steady pressure, ensuring sealant is pushed into the joint.
3. Tool with a spatula dipped in detergent water within 5-10 minutes of application.
4. Clean up with turps before product skins.
5. Sealant will cure in 72 hours

# Selleys Wet Area Silicone

---

## Tips

- For neater joints, mask sides before applying sealant and remove tape before sealant skins.
- Sealant must be cleaned regularly to avoid build-up of soap scum.

## Clean Up

Uncured product may be removed with mineral turpentine. Cured product can be removed with Selleys Silicone Remover or by cutting and scraping.

## Storage

Store in a dry place, below 30°C. Use within 6 months of opening.

## Limitations

- Not paintable. Complete painting 7 days prior to applying sealant
- Not suitable for use on PP, PE, PTFE
- Not suitable for aquariums
- Not suitable for food or drinking water contact
- Not suitable for permanent water immersion

## Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)

**\*25 Year Guarantee** when used as directed for private use and within 12 months of purchase, this product is guaranteed against crumbling, cracking or peeling away. If the product does not perform as specified within the relevant warranty period, we will replace the goods free of charge. To make a claim under the warranty, please contact Selleys and provide details of your claim. You must show proof of purchase and bear all expenses incurred in making a claim.

The benefits of this warranty are in addition to the rights and remedies under any applicable law. Our

goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.