

No Mould Silicone Sealant

Description

Selleys No Mould silicone sealant is specially designed to create long lasting waterproof seal in areas where mould resistance is necessary. Selleys No Mould contains Speed Seal technology producing a shower ready seal in 1 hour.

Product Information

Packaging	Size	Colour
Cartridge	290mL	Transparent
Cartridge	290mL	White
Tube	100mL	Transparent
Tube	100mL	White

Uses

This is the perfect product for humid and damp environments such as kitchens and bathrooms, where mould is normally present.

Technical Features

- Stops mould growth (soap scum and dirt must be regularly cleaned off)
- Shower ready in 1 hour
- Long lasting water proof seal
- Resists lifting
- Acetic cure

Technical Details

Property	Typical Result
Technology	Acetic cure silicone sealant
Skin time	20 minutes
Curing Rate	2mm / 24 hours
Joint Movement Capability (ISO 9047)	+/- 25%
Elongation (ASTM D412 modified)	Approximately 400%
Indicative data only, not intended for preparation of specifications	

How To Use

1. Before applying your new sealant, we recommend spraying Selleys Rapid Mould Killer™ into the gap to kill any residual mould.
2. Thoroughly clean surface where sealant will be applied with turps and dry.
3. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle.
4. Place in caulking gun, and apply with steady pressure, ensuring sealant is pushed into the joint.
5. Tool with a spatula dipped in detergent water within 10 minutes of application.
6. Clean up with turps before product skins. Sealant will be waterproof and shower ready in 1 hour after application in showers. The semi-cured sealant must not be touched until fully cured (at least 48 hours).
7. To maintain your sealant properties, ensure you regularly clean off any soap scum and dirt as these encourage mould growth.

Clean Up

Uncured product may be removed with mineral turpentine. Cured product can be removed with Selleys Silicone Remover or by cutting and scraping.

Handy Hints

- For neater joints, mask sides before applying sealant and remove tape before sealant skins.
- Sealant must be cleaned regularly to avoid build-up of soap scum and dirt.

Limitations

- Not paintable. Complete painting 7 days prior to applying sealant.
- Not suitable for aquariums.
- Not suitable for food and drinking water contact.
- Not suitable for permanent water immersion.
- Not suitable for metals other than aluminium and stainless steel.

Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – www.selleys.com