

# SELLEYS STORM – WHITE, GREY & BLACK

## Description

Storm™ Sealant with Sil-X™ technology delivers an immediate waterproof seal on any building material\*, wet or dry, indoors or outdoors. It can even be applied in the rain to stop leaks in an instant.

## Product Information

Packaging	Size	Colour
Cartridge	290mL	White
Cartridge	290mL	Grey
Cartridge	290mL	Black

## Uses

- For sealing, bonding and filling
- Suitable for wet or dry surfaces
- For interior/exterior applications
- Suitable for use on glass, metal, timber, brick, concrete, tiles and most plastics#

## Technical Features

- Waterproof
- Weather resistant
- Highly flexible
- Highly versatile
- For indoor & outdoor
- Paintable
- UV resistant
- Mould resistant
- Low odour
- Stops & prevents leaks
- Non-slumping

## Technical Details

Property	Typical Result
Technology	Moisture curing silyl-modified polymer (SMP)
Colour	White, Grey & Black
Density	~1.60

Application Temperature	5 to 35°C
Tooling Time (23°C, 50% R.H.)	~15minutes
Skin Time (23°C, 50% R.H.)	15 to 30minutes
Cure Rate (23°C, 50% R.H.)	2.5 to 3mm/24hrs
Slump	0mm
Tensile Strength (DIN 53504)	1.5 ± 0.3MPa
Shore A Hardness	40 - 50
Elongation at Break (DIN 53504)	>250%
Modulus at 100% Elongation (DIN 53504)	1.3 ± 0.2MPa
Movement Capability (ISO9046 modified)	± 20%
Service Temperature	0 to 70°C
VOC Content (By theoretical calculations)	~49g/L
Indicative data only, not intended for preparation of specifications	

## Surface Preparation

Ensure surface is clean, dry and free from dust, grease, old or crumbling sealant.

## Directions for Use

- Cut tip and attach nozzle. Insert into a caulking gun.
- Cut nozzle to required size.
- Apply with a caulking gun, pushing sealant into joint or gap.
- Smooth off using a spatula dipped in turps or white spirit within 5 minutes of applying.

# SELLEYS STORM – WHITE, GREY & BLACK

---

## Tips

- For neater joints, mask sides before applying sealant and remove tape before sealant skins.
- If painting, paint with two coats of a quality water-based exterior paint.

**Note:** Forms an instant seal but must not be disturbed until cured (~48hours).

## Clean Up

- Clean up with turps before sealant cures.
- Cured sealant can be removed by scraping or sanding or with the help of Selleys Silicone Remover.

## Storage

- Store in cool, dry conditions below 30°C.
- Use within 6 months of opening.

## Limitations

- Cannot be painted with solvent based paints. If required, paint with a water-based paint first.
- #Not for Polyethylene, Polypropylene or Teflon.

## Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)